

3M™ FLOOR PAD SELECTION GUIDE FOR NOBLES®

Nobles floor scrubbers have multiple machine head types to optimize cleaning performance for specific areas. 3M™ Floor Pads offer application specific choices for stripping, scrubbing and cleaning.



MAINTENANCE FOR FLOORS WITH CONVENTIONAL COATED FINISHES

| | Stripping | Scrubbing | Cleaning |
|--|--|---|---|
| | Removes all layers of floor finish when used with a floor stripper chemical. | Removes up as much as 1-4 coats of finish with water or neutral cleaner and multiple passes. Leaves a clean surface ready for recoating. | Designed for daily use to help remove surface soils without dulling surface. |
| | 3M™ High Productivity Pad 7300* | Scotch-Brite™ Surface Prep Pad* | 3M™ Red Buffer Pad 5100* |
| | <ul style="list-style-type: none"> • Our most aggressive stripping pad • For fast finish removal and consistent stripping • Open construction resists loading and clogging | <ul style="list-style-type: none"> • Removes 2 - 4 coats of finish with multiple passes • For heavy duty scrubbing before recoating | <ul style="list-style-type: none"> • Designed for everyday cleaning and light scrubbing • Removes light soil, scuff marks and black heel marks |
| | 3M™ Brown Stripper Pad 7100 | 3M™ Blue Cleaner Pad 5300 | 3M™ White Super Polish Pad 4100 |
| | <ul style="list-style-type: none"> • Conformable stripping pad for uneven floors • For stripping prior to refinishing | <ul style="list-style-type: none"> • Removes 1 - 2 coats of finish with multiple passes • For heavy duty scrubbing before recoating | <ul style="list-style-type: none"> • For light cleaning with minimal dulling of finish • Helps remove soil and scuff marks • Can also be used to polish wood floors |
| | PROCEDURE | PROCEDURE | PROCEDURE |
| | <ol style="list-style-type: none"> 1. Dust mop 2. Mask off delicate surfaces 3. Apply properly diluted stripping solution 4. Let solution dwell per instructions 5. Strip with floor machine and pad 6. Pick up dirty solution 7. Detail damp mop 8. Let dry and dust mop before applying finish | <ol style="list-style-type: none"> 1. Dust mop 2. Use properly diluted scrubbing solution 3. Scrub with floor machine and pad 4. Pick up dirty solution 5. Detail damp mop 6. Let dry and dust mop before applying finish | <ol style="list-style-type: none"> 1. Dust mop 2. Use properly diluted cleaning solution 3. Clean with floor machine and pad 4. Pick up dirty solution 5. Let dry before buffing or burnishing |

*Recommended for most applications. For softer materials such as rubber or sheet vinyl, follow flooring manufacturer's recommendations.

MAINTENANCE FOR UNCOATED POROUS STONE FLOORS TERRAZZO • MARBLE • POLISHED CONCRETE**

| Polish and Restore | | | Alternative Method | Cleaning and Polishing |
|--|--|---|--|--|
| STEP 1 | STEP 2 | STEP 3 | Scotch-Brite™ Sienna Diamond Floor Pad Plus | Scotch-Brite™ Purple Diamond Floor Pad Plus |
| 3M™ Trizact™ Diamond HX Discs Gold | 3M™ Trizact™ Diamond HX Discs Red | 3M™ Trizact™ Diamond HX Discs Blue | | |
| <ul style="list-style-type: none"> • Coarse abrasive • For heavily damaged floors with visible wear or scratches | <ul style="list-style-type: none"> • Medium abrasive • For floors with less damage | <ul style="list-style-type: none"> • Fine abrasive • For final polishing before burnishing with Scotch-Brite™ Purple Diamond Floor Pad Plus | <ul style="list-style-type: none"> • Diamond-coated pad cleans and conditions worn and dull concrete, marble, terrazzo and other porous stone flooring • Use before Scotch-Brite™ Purple Diamond Floor Pad Plus to bring floor to a medium shine if 3M™ Trizact Diamond HX Discs are not used during the restorative process | <ul style="list-style-type: none"> • Diamond-coated pad for periodic maintenance • For use with low and high speed equipment • Helps bring floors to a high shine |
| | | | | 3M™ Red Buffer Pad 5100* |
| | | | | <ul style="list-style-type: none"> • Designed for everyday cleaning and light scrubbing • Removes light soil, scuff marks and black heel marks |

** For detailed instructions on use, visit www.3m.com/facility

DISCLAIMERS:

Product Use: Many factors beyond 3M™'s or Nobles's control and uniquely within user's knowledge and control can affect the use and performance of a 3M™ product in a particular application. Given the variety of factors that can affect the use and performance of a 3M™ product, user is solely responsible for evaluating the 3M™ product and determining whether it is fit for a particular purpose and suitable for user's method of application.

Warranty, Limited Remedy and Disclaimer: Many factors beyond 3M™'s or Nobles's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. User is solely responsible for evaluating the 3M™ product and determining whether it is fit for a particular purpose and suitable for user's method of application. Unless an additional warranty is specifically stated on the applicable 3M™ product packaging or product literature, 3M™ warrants that each 3M™ product meets the applicable 3M™ product specification at the time 3M™ ships the product. 3M™ MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. If the 3M™ product does not conform to this warranty, then the sole and exclusive remedy is, at 3M™'s option, replacement of the 3M™ product or refund of the purchase price.

Limitation of Liability: Except where prohibited by law, neither 3M™ or Nobles will be liable for any loss or damage arising from the 3M™ product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.