SPEED SCRUB® 350 | STAND-ON SCRUBBER



Product Specifications

Feature	20 in / 500 mm Single Disk Self Propel	24 in / 600 mm Dual Disk Self Propel	
Cleaning Tool Attachment	Insta-Click™ Standard		
Machine Speed Top Scrub and Forward Transport Top Reverse Transport	3.6 mph (5.8 km/hr) 1.1 mph (1.8 km/hr)		
Scrubbing Coverage Rate Per Hour Theoretical Max Conventional - Practical ec-H2O NanoClean® - Practical	31,680 ft2 (2,946 m2) 24,588 ft2 (2,287 m2) 25,284 ft2 (2,351 m2)	38,016 ft2 (3,535 m2) 30,052 ft2 (2,795 m2) 30,903 ft2 (2,874 m2)	
Control Panel			
Pro-Membrane™	Standard		
LCD Pro-Panel® Touch Screen	Optional		
Brush/Pad Drive System			
Cleaning Path	20 in / 500 mm	24 in / 600 mm	
Pad/Brush RPM	215 rpm	275 rpm	
Pad/Brush Down Pressure	62 & 90 lbs (28 & 41 kg)	64 & 91 lbs (29 & 41 kg)	
Scrub Motor	24 VDC, 0.87 HP / 0.65 kW		
Solution and Recovery Systems			
Solution Tank Capacity	14.1 gal (53 L)		
Recovery Tank Capacity	18.4 gal (70 L)		
Drive Motor	24 VDC, 0.64 HP / 0.48 kW		
Vacuum Motor	24 VDC, 0.62 hp / 0.46 kW		
Vacuum Water Lift	42 in (1,067 mm)		
Cleaning Technology			
Conventional	Standard		
ec-H2O NanoClean® Technology	Optional		
Conventional Water Flow	0.15 / 0.35 / 0.50 gpm 0.57 / 1.32 / 1.89 lpm		
ec-H2O NanoClean® Technology Water Flow	0.12 / 0.25 / 0.35 gpm 0.45 / 0.95 / 1.32 lpm		

Feature Battery System	20 in / 500 mm Single Disk Self Propel	24 in / 600 mm Dual Disk Self Propel	
battery system			
System Voltage / Battery Count	24 Volts / 4		
Batteries	Wet 210 AH Wet 240 AH (Provides longest run time) Sealed AGM 220AH		
Battery Run Time (Up to Hours)	3.1	4.0	
On-Board Charger	Yes	Yes	
Off-Board Charger	Yes	Yes	
Decibel Ratings At Operator Ear			
Standard - dBA	63.7	64.5	
Quiet-Mode™ - dBA	59.7	61.3	
Machine Dimensions and Weights			
Overall Width with Squeegee	30.1" / 765 mm	31.2" / 793 mm	
Length X Width X Height	55 X 26.5 X 49 Inches 1,397 X 673 X 1,245 mm		
Weight (less batteries)	490 lbs / 222 kg	495 lbs / 225 kg	
Weight (with batteries)	725 lbs / 329 kg	730 lbs / 331 kg	
Product Backing			
Warranty	10 years Rotomold - 3 years Parts 2 years Labor - 6 months of Trip		

Specifications are subject to change without notice.