



Commercial Floor Care Equipment

## Speed Scrub™ 2401 & 2601 Automatic Scrubbers



Features		Specifications
<b>Product Name</b> <b>Model Number</b>	<b>Speed Scrub™ 2401</b> <b>612216/Canadian#612100/FaST™#613386</b>	<b>Speed Scrub™ 2601</b> <b>612219/Canadian #612496/FaST™#613385</b>
<b>Chassis/Body Construction</b> Chassis Construction: Casters: Drive Wheel:	Rotationally-molded polyethylene (2) 4 in/10 cm diameter x 1-1/2 in 3.8 cm (2) 8 in /20 cm diameter x 2 in/ 5 cm	Rotationally-molded polyethylene (2) 4 in/10 cm diameter x 1-1/2 in 3.8 cm (2) 8 in /20 cm diameter x 2 in/ 5 cm
<b>Dimensions</b> Product Height: Product Length: Product Width: Product Weight:	39 in /99.06 cm 50 in /127 cm 26 in /66.04 cm 375 lb w/o batteries /170.1 kg 600 lb with batteries /272.16 kg	39 in / 99.06 cm 50 in /127 cm 28 in /71.12 cm 375 lb w/o batteries /170.1 kg 600 lb with batteries /272.16 kg
<b>Productivity</b> Cleaning Rate Per Hour: (excludes dump/fill cycles) Cleaning Width:	24,000 ft² / 2229.6 m² per hour 23-1/8 in / 58.73 cm	26,000 ft² / 2415.4 m² per hour 25-1/8 in / 63.80 cm
<b>Battery System</b> Battery Amp Hour Rating: Battery Count: Battery Description:  Battery Run Time Per Charge: Charging Unit Description:	215 A 2 12 V, deep cycle lead acid batteries with rope handles Up to 4-3/4 hours 20 A automatic charge	215 A 2 12 V, deep cycle lead acid batteries with rope handles Up to 4-3/4 hours 20 A automatic charger
<b>Brush/Pad Drive System</b> Brush/Pad Diameter: Motor Amps: Motor Hp: Motor Volts: Motor RPM: Brush/Pad Pressure:	(2) 12 in / 30.48 cm 15 A .75 hp 24 V 220 rpm Variable; 40 - 150 lb / 18 - 68 kg	(2) 13 in / 33.02 cm 15 A .75 hp 24 V 220 rpm Variable; 40 - 150 lb / 18-68 kg
<b>Decibel Rating</b> Ten Foot Rating: Five Foot Rating: Operator's Position Rating:	70 dBa 73 dBa 75 dBa	70 dBa 73 dBa 75 dBa
<b>Solution Delivery System</b> Max Sol. Flow Rate- Conventional Sol. Flow Rate - FaST™	.75 gpm/ .284 L/min .15 gpm / .04 L/min	.75 gpm/ .284 L/min .15 gpm / .04 L/min

Nobles • 12875 Ransom Street • Holland, MI 49424 • USA • (800)522-7839 • Fax (616)786-2345  
Specifications Subject to Change Without Notice.

Solution Capacity:	17 gal / 64.35 L	17 gal / 64.35 L
<b>Recovery System</b> Recovery Capacity: Squeegee Width:	17 gal / 64.35 L 33 in / 84 cm	17 gal / 64.35 L 33 in / 84 cm
<b>Options and Kits</b> <b>Recycling Kit:</b> (not available for FaST™ machine)	Field installed; #604780	Field Installed; #604780
<b>Total Power Consumption</b> Power Consumption Amps:	45 A nominal	45 A nominal
<b>Transport Drive System</b> Transport Drive System Description: Speed Control System:	.5 hp trans axle Variable 0 - 230 feet per minute	.5 hp trans axle Variable 0 - 230 feet per minute
<b>Vacuum System</b> Airflow: Waterlift: Vacuum Motor Type: Vacuum Motor Hp: Vacuum Motor Amps: Vacuum Motor Stages: Vacuum Motor Volts: Vacuum Motor Watts:	69 cfm / 1.95 m <sup>3</sup> 68 in / 172.72 cm 5.7 in / 14.5 cm diameter; tangential discharge 3/4 hp, 3 A stage 21 A 3 stage 24 V 560 watts	69 cfm / 1.95 m <sup>3</sup> 68 in / 172.72 cm 5.7 in / 14.5 cm diameter; tangential discharge 3/4 hp, 3 A stage 21 A 3 stage 24 V 560 watts
<b>Warranty</b>	<b>10 years</b> – Nobles warrants the rotationally-molded polyethylene housings and parts on all of its machines to be free from defects in materials and workmanship, under normal use and service for ten <b>(10)</b> years to the original end user. <b>3 years</b> – Nobles guarantees the performance of non-polyethylene parts and components to be free from defects for up to three <b>(3)</b> years or 2,500 hours of operation. <b>3 years</b> – Labor charges are covered for three <b>(3)</b> full years from the date of purchase for Nobles products, provided an authorized Nobles/Tennant service provider is used for repair. Travel is covered for <b>(90 days)</b> .	