



Portapac® I and II

specifications



Vacuum System		Portapac® I	Portapac® II
Airflow at orifice		94 cfm / 2.66 m³/h	101 cfm / 2.86 m³/h
Waterlift at sealed orifice		90 in / 2280 mm	114 in / 2890 mm
Vacuum motor amps		7.5 A	10 A
Vacuum motor horsepower		1.15 hp	1.7 hp
Vacuum motor stages		2	
Vacuum motor watts		900 watts	1200 watts
Debris Recovery System			
Vacuum bag capacity		0.2 bushels	
Vacuum bag description		Equipped with paper filter bag, 5-quart capacity	
Vacuum bag filtration		99.9% efficient @ 0.3 microns. Optional HEPA filter; 99.97% efficient @ 0.3 microns	
Vacuum hose length		5 ft /1.52 m	
Productivity			
Maximum coverage rate per hour		7, 300 ft²/h	
Power System			
Amps		7.5 A	10 A
Voltage		120 Volts	
Watts		900 watts	1200 watts
Power cord length		50 ft / 15.24 m	
Power cord type		16 gauge; 3 wire SJTO, non-marking yellow; detachable; UL listed	
Standard/Optional Accessories			
Standard equipment		5 ft / 1.52 m vacuum hose; shoulder straps and waist harness; electric power nozzle receptacle; detachable 50 foot / 15.24 m power cord with belt clip and one paper vacuum bag.	
Optional accessories		HEPA attachment kit, blower attachment kit, waist extension belt, reusable cloth bag, standard attachment kit and air-driven turbo brush floor tool.	
Dimensions / Weight / Sound level			
Length		8.5 in / 215.9 mm	
Width		7.5 in / 190.5 mm	
Height		23.5 in / 596.9 mm	
Net weight		11 lb / 4.99 kg	12 lb / 5.45 kg
Sound level		75 dBA	
Warranty		3 years/2500 hrs on parts and labor (excluding batteries). 10 years on rotationally-molded polyethylene tanks.	