


NOTES:
1) SPECIFIED MANUFACTURERS:
BERGQUIST.
MANUFACTURER MATERIAL SPEC: SP900S

- 2) MATERIAL SPECIFICATIONS:
- THERMAL CONDUCTIVITY: 1.6 W/m-k OR BETTER.
 - OPERATING TEMPERATURES: -25 C TO +125C OR BETTER.
 - THERMAL IMPEDANCE: 0.61 C- IN^ 2/W @ 50 PSI OR HIGHER.
 - DIELECTRIC BREAKDOWN VOLTAGE (VAC) = 5500.
 - FLAME RATING: V - 0

3) SIMILAR TO TENNANT #1201177.



PENDING RELEASE

MATERIAL SPECIFICATIONS:		OTHER TREATMENTS AND FINISHES		PAINT - COLOR		CHANGED BY: JOHN HAEG	DATE: 03/27/2013	WELDING NOTATION IN ACCORDANCE WITH AWS A2.4-98	GENERAL NOTES PRIMARY DIMENSIONS ARE METRIC, REFERENCE DIMENSIONS WITH BRACKETS ARE INCH. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE AFTER TREATMENTS AND FINISHES.	
PART NAME: PAD, SIL, CIRCUITBOARD, COMBO [T17]		GLOSS		PERFORMANCE	ACCEPTANCE	MDR:	01/02/2014			
						DES: JOHN HAEG				