



5400

FaST™ Detergent Pump Replacement Kit

This kit is designed to retrofit 5400 FaST™ machines that are equipped with a detergent pump that has been discontinued.

INSTALLATION INSTRUCTIONS:

Installation Time: 1 hour

TOOLS REQUIRED: 13mm & 9/16" Wrench, Pliers, Standard Screwdriver and Wire Cutters.

KIT CONTENTS

P/N.	Description	Qty.
1005413	PUMP, DETERGENT, 24VDC	1
613947	HOSE, PVC CLR, .125ID .38ODX24"	1
613720	HOSE, VYL, .19ID .38ODX2"	1
613717	HOSE, PVC, BRD, .38ID .60ODX2"	2
391443	HOSE, PVC, BRD, .38ID .60ODX17"	1

1. Drain tanks, remove batteries and carefully turn machine upside down.

FOR SAFETY: When servicing machine, wear safety glasses and protective gloves when handling batteries. Use adequate assistance when turning machine over.


2. Remove the transaxle and the squeegee mounting bracket assembly in order to access the FaST™ solution system.

3. Remove the FaST™ solution system parts that are outlined in the "BEFORE" diagram.

4. Install the pump replacement kit as shown in the "AFTER" diagram.

5400 FaST™ Solution System

Slide hose over shoulder and secure with clamp



PUMP DETAIL

Connect wires to these terminals

