



# Speedshine®

## specifications



| Models                                     | 1700HD                                                                                                     | 2000HD                                      |
|--------------------------------------------|------------------------------------------------------------------------------------------------------------|---------------------------------------------|
| Brush RPM                                  |                                                                                                            | 175 rpm                                     |
| Motor volts                                |                                                                                                            | 120 volts                                   |
| Motor hp                                   |                                                                                                            | 1.5 hp / 1.12 kW                            |
| Motor amps                                 |                                                                                                            | 12 A                                        |
| Motor type                                 | AC, 66 frame, heavy duty, circuit breaker protected; triple planetary; precision gear box, 10:1 gear ratio |                                             |
| Motor watts                                |                                                                                                            | 1100 watts                                  |
| <b>Solution Delivery System</b> (optional) |                                                                                                            |                                             |
| Tank volume                                |                                                                                                            | 3 gal / 11.36 L                             |
| Nominal solution flow rate                 |                                                                                                            | 0.1 gpm / 0.38 L / min                      |
| Coverage rate per tank                     | 1000 sq ft / 92.9 sq m per tank                                                                            | 1500 sq ft / 135.35 sq m per tank           |
| <b>Productivity</b>                        |                                                                                                            |                                             |
| Max. coverage per hour                     | 2000 ft <sup>2</sup> / 185.8 m <sup>2</sup>                                                                | 3000 ft <sup>2</sup> / 278.7 m <sup>2</sup> |
| <b>Power System</b>                        |                                                                                                            |                                             |
| Power cord length                          |                                                                                                            | 50 ft / 15.24 m                             |
| Power cord description                     |                                                                                                            | 14 gauge, 3-wire, SJT                       |
| <b>Dimensions / Weight / Sound level</b>   |                                                                                                            |                                             |
| Height                                     | 48 in / 1219 mm                                                                                            | 48 in / 1219 mm                             |
| Length                                     | 22.75 in / 578 mm                                                                                          | 23.5 in / 597 mm                            |
| Weight                                     | 97 lb / 44 kg                                                                                              | 100 lb / 45.36 kg                           |
| Width                                      | 17 in / 403 mm                                                                                             | 20 in / 510 mm                              |
| Sound level (operator's ear)               | 60 dBa                                                                                                     | 60 dBa                                      |
| <b>Warranty</b>                            |                                                                                                            |                                             |
|                                            | 3 years/2500 hrs on parts and labor.<br>10 years on rotationally-molded polyethylene parts.                |                                             |