



Model R3 Specifications

Cord Electric ReadySpace®

Feature		English / Metric
Brush Drive System		
Roller diameter		4 in / 110 mm
Roller length		15 in / 380 mm
Roller motor power (2 motors)		.3 hp / .22 kW (each)
Roller RPM		450 rpm
Motor RPM		1600 rpm
Chassis/Body Construction		
Chassis construction	Cast aluminum frame, rotational molded tanks and injection molded plastic cover	
Wheel descriptions		8 in / 200 mm
Vacuum System		
Airflow at orifice		99 cfm / 2.8 m³/min
Vacuum motor amps		7.1 amps / 3.6 amps
Vacuum motor power		1.2 hp / .89 kW
Vacuum motor stages		2 stage
Sealed waterlift		86 in / 2180 mm
Machine Dimensions (Handle folded flat for storage)		
Length		30 in / 750 mm
Machine Width		19 in / 490 mm
Height		28 in / 710 mm
Weight		117 lb / 53 kg
Solution & Recovery System		
Solution tank capacity		5 gal / 19 L
Recovery tank wet capacity		5 gal / 19 L
Spray jet count		1-quick connect
Power Consumption		
Amps		11 amps / 5.5 amps
Voltage		120 V / 230 V
Watts		1320 watts
Cord		50 ft / 15 m
Electrical Safety Approval		ETL Tested for UL & CSA Standards
Pump System		
Solution pump pressure		65 psi / 4.48 bar
Solution pump amps		.5 amp / .25 amp
Solution pump flow rate		.2 gpm / .76 L/min
Sound Level*		
Decibel rating @ operators ear		69 dBA
Warranty	3 YEARS/2500 HRS ON PARTS AND LABOR. 10 YEARS ON ROTATIONALLY-MOLDED POLYETHYLENE TANKS. NO TRAVEL. PLEASE CONTACT COMPANY FOR MORE WARRANTY INFORMATION.	

* Sound levels per ISO 11201 as recommended by the American Association of Cleaning Equipment Manufacturers & OSHA