



## ATLV® 4300 Specifications | All-Terrain Litter Vacuum

### VACUUM SYSTEM

|                                         |                                      |
|-----------------------------------------|--------------------------------------|
| Type                                    | Vacuum nozzle                        |
| Time required to cover a football field | 1/2-hour                             |
| Debris hopper                           |                                      |
| Volume capacity                         | 110 gal   416 L                      |
| Bag capacity-each                       | 55 gal   208 L                       |
| Bag size                                | 44 x 55 in, 33 mm   1,120 x 1,400 mm |
| Nozzle size (diameter)                  | 8 in   200 rpm                       |
| Vacuum fan (diameter)                   | 17 in   430 mm                       |

### PROPELLING SYSTEM

|                                                      |                             |
|------------------------------------------------------|-----------------------------|
| Propel speed forward (variable to)                   | 16 mph   26 km/h            |
| Propel speed reverse (variable to)                   | 5 mph   8 km/h              |
| Engine-diesel, liquid cooled Kubota                  |                             |
| Gross Intermittent Power*                            | 18.5 kW (24.8 hp) @3000 rpm |
| Tennant Governed Power                               | 18.5 kW (24.8 hp) @3000 rpm |
| Engine-turbo diesel, liquid cooled Kubota (optional) |                             |
| Gross Intermittent Power*                            | 24.5 kW (32.8 hp) @3000 rpm |
| Tennant Governed Power                               | 24.5 kW (32.8 hp) @3000 rpm |
| Type                                                 | Hydrostatic                 |
| Motors                                               | Both rear wheels            |
| Hydraulic                                            |                             |
| Pumps                                                | 1 propelling, 1 accessory   |
| Oil cooler                                           | Fin type                    |
| Gradeability                                         |                             |
| Full & empty hopper                                  | 12 deg, 21%                 |

\* Per SAE J1995

### MACHINE SPECIFICATIONS

|                         |                     |
|-------------------------|---------------------|
| Length                  | 102 inch   2,590 mm |
| Width                   | 46 inch   1,170 mm  |
| Height                  | 84 inch   2,130 mm  |
| Weight-net base machine | 1,860 lb   844 kg   |
| Turning radius          | 18 inch   460 mm    |

### WARRANTY

See your local representative for warranty information.

Specifications subject to change without notice.

For a complete selection of genuine Tennant parts, please consult the ATL V 4300 Parts and Consumables Reference Guide.