## **T981** Ride-on Floor Scrubber-Dryer

## **Maneuverable and Productive**

T981 effectively scrubs and dries large hard-floor surfaces with light to medium dirt and stains. Its intuitive controls make it easy to operate and maintain. T981 is ideal for cleaning smooth floors in areas such as retail, logistics and light industry.





**Productivity Boost** Easily fit into the most congested spaces with small turning radius and get more cleaning done with the lead acid batteries that allow cleaning shifts up to 5 hours.



**Simple Operation** 

Easy start-up and quick training with one-button cleaning operation that lowers the scrub head and squeegee at the same time.



**Get the Right Solution** Choose between the 80 cm or 90 cm disk or 75 cm cylindrical scrub deck to fit T981 into your application.



## Inside the T981

- 1. Easily change water flow rate and other cleaning functions from intuitive control panel.
- 2. Multi-stage vacuum motor for strong water pick-up.
- 3. Quick, mess-free tank draining with large, pinch-style recovery tank drain hose.

4. Large solution tank with level gauge and drain hose.

- 5. Consistent water pick-up with durable parabolic squeegee design and standard Linatex<sup>®</sup> squeegee blades.
- 6. Simple no-tools, no-touch brush change system.



## **T981** Specifications

		SPECIFICATION	
FEATURE	Disk	Disk	Cylindrical
Cleaning path	80 cm	90 cm	75 cm
Productivity theoretical max	4800 m²/hr	5300 m²/hr	4300 m²/hr
Estimated coverage*	3570 m²/hr	3950 m²/hr	3100 m²/hr
Scrubbing speed		5.75 kmh	
Scrub head and squeegee raise/lower		independent actuators	
Brush speed	200 rpm		1000 rpm
Brush pressure	90 kg	100 kg	50 kg
Solution tank capacity		125 L	
Recovery tank capacity		135 L	
Battery run time - up-to hours 320Ah Wet Battery)**		5,5	
Battery voltage	36V 1x 36V or 6 x 6V		
Dimensions (LxWxH)	1720 x 1010 x 1360 mm	1720 x 1100 x 1360 mm	1810 x 1050 x 1360 mm
Squeegee width	1010 mm	1100 mm	1010 mm
Weight (with heaviest battery)	705 kg	707 kg	715 kg
External radius (wall to wall)	2270 mm	2310 mm	2430 mm
Maximum climbing angle		16%	
Sound level (operator's ear)***		72 dB	

Specifications subject to change without notice.

\* Estimated coverage rates use the practical speed and empty/fill time standards from the 2004 ISSA Cleaning Times handbook. \*\* Run times are based on Continuous Scrubbing Run Times.

\*\*\* Sound levels per ISO 11201 as recommended by the American Association of Cleaning Equipment Manufacturers & OSHA

TENNANT UK CLEANING SOLUTIONS LTD uk.tennantco.com

For a demonstration or additional information, call **01604 583191** or email **sales.uk@tennantco.com**