





Mid-size walk-behind scrubber-dryer

Productive and comfortable to operate

Get a lot of return on value with a mid-size scrubber with wide scrub head and large tank capacity. Featuring a simple control panel, comfortable ergonomics, and straight-forward operation. Daily cleaning routine is made easy due to large recovery tank access, easy spin-on, spin-off brush/pad replacement and yellow touchpoints. Perfect for mid-size retail stores, and schools.

Available technologies



Worry-free operation and maintenance with optional lithium ion batteries.



Productivity boost

Get more cleaning done compared to smaller scrubbers with wide scrub path and large solution tank capacity.



Comfortable & easy to maneuver

Maintain operator health and safety with great maneuverability, and maximize comfort with adjustable controls.



Sustainable performance

Reduce noise levels and water consumption while increasing run-time with ECO mode.

Inside the T391

- 1. Self-leveling scrub head for optimum cleaning performance.
- 2. Simplified operator training with easy-to-use preprogrammed cleaning settings, standard and ECO.
- 3. Monitor helpful machine **information** with intuitive and large LCD display.
- 4. Simple daily maintenance with large sized recovery tank opening enabling full access and visibility.
- 5. Excellent water pick-up from adjustable squeegee design and standard Linatex® blades.
- 6. Simple no-tools, no-touch brush/pad change system.



T391 specifications

FEATURE	SELF-PROPEL	SELF-PROPEL	SELF-PROPEL	
Cleaning path	600 mm	70	700 mm	
Productivity (per hour) theoretical max	2697 m²/hr	3142	3142 m²/hr	
Estimated coverage (per hour)*	1818 m²/hr	214	2147 m²/hr	
Scrubbing speed		4,5 kmh		
Scrub head raise/lower	manual w	ith foot pedal	electronic by actuator	
Brush/pad speed		200 rpm		
Brush/pad pressure	2	9 kg	35,4 Kg	
Solution tank capacity		70 L		
Recovery tank capacity		70 L		
Battery run time – up-to hours**		3.5 hrs		
Battery voltage		24V (2x12)		
Dimensions (L x W x H)	1279 x 653 x 1033 mm 1279 x 735 x 1033 mm		5 x 1033 mm	
Squeegee width	815 mm	815 mm 940 mm		
Weight (with heaviest battery)	183 kg 187 kg			
Sound level (operator's ear)***		56 dB		

^{**}Estimated coverage rates use the practical speed and empty/fill time standards from the 2004 ISSA Cleaning Times handbook.

**Run times are based on Continuous Scrubbing Run Times.

***Sound levels per ISO 11201 as recommended by the American Association of Cleaning Equipment Manufacturers & OSHA

T391 lithium-ion specifications

FEATURE	SELF PROPEL		
Cleaning path	700	700 mm	
Productivity (per hour) theoretical max	3142	3142 m²/hr	
Estimated coverage (per hour)*	2147	2147 m²/hr	
Scrubbing speed	4,5	4,5 kmh	
Scrub head raise/lower	manual wit	manual with foot pedal	
Brush/pad speed	200	200 rpm	
Brush/pad pressure	29	29 kg	
Solution tank capacity	71	70 L	
Recovery tank capacity	71	70 L	
Battery Type	50 Ah Lithium-lon	90 Ah Lithium-Ion	
Charger Type	Off board charger	On board charger	
Battery charging time up-to hours**	2h	7h	
Battery run time - up-to hours**	1h30	2h30	
Battery voltage	2	27,8	
Dimensions - L x W x H	1279 x 735	1279 x 735 x 1033 mm	
Squeegee width	940	940 mm	
Weight (with heaviest battery)	18	185kg	
Sound level (operator's ear)***	56 dB		
Chemical dosina	Standard with ec-H2O	Standard with ec-H2O NanoClean® technology	

For a demonstration or additional information, call +32 3 217 94 11 or email europe@tennantco.com

Specifications subject to change without notice.

*Estimated coverage rates use the practical speed and empty/fill time standards from the 2004 ISSA Cleaning Times handbook.

**Run times are based on Continuous Scrubbing Run Times.

***Sound levels per ISO 11201 as recommended by the American Association of Cleaning Equipment Manufacturers & OSHA