



X4 ROVR SPECIFICATIONS

AUTONOMOUS FLOOR SCRUBBER

Operating system	BrainOS®
Learning type	Teach & Repeat and Area Fill
Scrubbing path	500 mm dual disk
Estimated coverage per solution tank	1,860m ²
Squeegee	551 mm
Solution tank	38 L
Recovery tank	38 L
Demisting chamber	11.4 L
Brush/pad rpm	220 rpm
Brush/pad downforce	up to 19 kg
Battery	Lithium-Ion, 90 Ah (qty: 1)
Cleaning tool attachment	Insta-Click®
Autonomous scrubbing battery time	up to 2.5 hrs
Autonomous solution delivery system	Velocity-controlled
Conventional scrubbing - pumped solution flow rates	Low: 0.08-0.18 GPM variable Med: 0.08-0.24 GPM variable High: 0.08-0.35 GPM variable
Charger type	on-board
Charger specs	50/60Hz, 100-240 VAC
System voltage	25.6 volts
Vacuum motor	0.45 kW
Standard sound level	as low as 66dBA
Aisle navigation	as low as 71 cm
Aisle entrance (90 degree)	as low as .91 m
Aisle u-turn	as low as 1.37 m
Machine height	112 cm
Machine length	96 cm
Machine width	56 cm
Autonomous distance to wall	as low as 7.6 cm
Weight (tanks empty, with battery)	183 kg

For a complete selection of genuine Tennant parts, brushes and pads, please consult the X4 ROVR Parts and Consumables Reference Guide

Tennant Australia

Unit 2, 10 Johnston Crescent
Horsley Park NSW 2175
T: 1800 226 843 (FREE CALL)
T: +61 2 9839 9700
www.tennantco.com.au
contactus@tennantco.com

Tennant New Zealand

18 Onslow Ave, Papatoetoe,
Auckland, 2104
T: +64 9 253 9013
F: +64 9 253 9015
www.tennantco.co.nz
contactus@tennantco.com