



Model 3050 Specifications

BACKPACK VACUUM

Feature		English / Metric
Vacuum System		
Airflow @ Orifice		101 cfm/ 2.86 m³/h
Waterlift at sealed Orifice		114-inch/2895 mm
Vacuum motor amps		10 A
Vacuum power		1.6 hp/ 1.19 kW
Vacuum motor voltage		120 V
Vacuum motor stages		2 stage
Vacuum motor type		Thru-flow, thermally protected, clean air design, UL recognized
Vacuum motor diameter		5.7-inch/ 144 mm
Chassis & Body Construction		
Chassis construction		Rotationally-molded polyethylene
Metal parts coating		Zinc-plated, epoxy powder coating
Vacuum Noise Rating		
Ten foot decibel rating		61 dBa
Operators position decibel rating		75 dBa
Machine Dimensions		
Length		8.5-inch/ 215 mm
Machine Width		7.5-inch/ 190 mm
Height		23.5-inch/ 595 mm
Weight		12 lb/ 5.44 kg
Dirt/Debris Recovery System		
Vacuum bag filtration description		Vacuum Bag 99.9% efficient at 0.3 microns. Optional HEPA filter; 99.97% efficient @ 0.3 microns
Vacuum bag description		Equipped w/ paper filter bag, 5 quart capacity
Vacuum bag capacity		0.2 bushel/ 7.04 liter
Recovery System		
Vacuum hose length		5 ft/ 1.5 m
Power Cord		
Power cord type		16 gauge; 3 wire SJTO, non-marking yellow; detachable; UL -listed
Power cord length		50 ft/ 15.24 m
Total Power Consumption		
Power consumption amps		10 A
Power consumption voltage		120 V
Power consumption watts		1200 watts
Warranty		3 YEARS/2500 HOURS PARTS AND LABOR. NO TRAVEL. 10 YEARS ON ROTATIONALLY-MOLDED POLYETHYLENE TANKS. PLEASE CALL FOR MORE WARRANTY INFORMATION