

Click the model number below...

3110 (single motor)

3120 (dual motor)



Model 3110 Specifications

LIGHTWEIGHT COMMERCIAL UPRIGHT VACUUM

Feature		English / Metric	
Model Names			
Models (single motor uprights)		12-inch/ 305 mm	15-inch/ 380 mm
Brush Drive System			
Belt description		Cogged/ gear drive belt	
Brush		Dynamically balanced for lowest noise & vibration at high rpm. Chevron bristle design converges debris to the vacuum nozzle intake	
Brush motor power (DMUs)		180 watts	
Brush RPM		4500 rpm (avg.)	
Vacuum System			
Airflow-motor		92 cfm/ 42 L/sec	
Waterlift-motor		79-inch/ 2000 mm	
Waterlift-machine		59-inch/ 1500 mm	
Vacuum motor type		2-stage	
Vacuum motor power		1.14 hp/ 0.85 kW	
Chassis & Body Construction			
Chassis & Body Construction		Injection-molded Bayblend® (ABS & polycarbonate) & ABS	
Vacuum Noise Rating			
Operators position decibel rating		69 dBa	
Machine Dimensions			
Length		13-inch/ 330 mm	
Machine Width		12-inch/ 305 mm	15-inch/ 380 mm
Height		44-inch/ 1115 mm	
Weight (w/ cord)		17.9 lb/ 8.1 kg	18.4 lb/ 8.3 kg
Weight (w/o cord)		16.6 lb/ 7.5 kg	17.1 lb/ 7.7 kg
Handle weight		2.5 lb/ 1.1 kg	
Debris Recovery/ Filtration			
Vacuum bag capacity		1.2 gallon/ 4.5 liter	
Vacuum bag description		3-ply paper micro filter bag w/ “Bag Full/Blockage” indicator light	
Vacuum filtration		Standard 5-level filtration: 3-play paper filter bag, washable foam intake filter, 3M Filtrete®, exhaust microfilter together yield 98% @ 0.3 micron size filtration	
Recovery System			
Vacuum hose length		15-inch/ 380 mm: stretches to 63-inch/1600 mm	
Vacuum wand		Telescopic 21-inch/ 533 mm to 35-inch/ 890 mm	
Power Cord			
Power cord length		49 ft/ 14935 mm	
Power cord type		17 gauge, 3 wire SJT, safety yellow, UL-listed	
Warranty		1 YEAR ON PARTS AND LABOR. 1 YEAR ON ROTATIONALLY-MOLDED POLYETHYLENE TANKS. NO TRAVEL. 3 YEARS LIMITED WARRANTY ON ELECTRIC MOTOR AND BELTS NOT SUBJECT TO WEAR. PLEASE CONTACT COMPANY FOR MORE WARRANTY INFORMATION.	



Model 3120 Specifications

LIGHTWEIGHT COMMERCIAL UPRIGHT VACUUM

Feature		English / Metric		
Model Names				
Models (dual motor uprights)		12-inch/ 305 mm	15-inch/ 380 mm	18-inch/ 455 mm
Brush Drive System				
Belt description		Cogged/ gear drive belt		
Brush		Dynamically balanced for lowest noise & vibration at high rpm. Chevron bristle design converges debris to the vacuum nozzle intake		
Brush motor power (DMUs)		180 watts	180 watts	200 watts
Brush RPM		5000 rpm	5000 rpm	4500 rpm (avg.)
Vacuum System				
Airflow-motor		92 cfm/ 42 L/sec		
Waterlift-motor		79-inch/ 2000 mm		
Waterlift-machine		59-inch/ 1500 mm		
Vacuum motor type		2-stage		
Vacuum motor power		1.07 hp/ 0.8 kW		
Chassis & Body Construction				
Chassis & Body Construction		Injection-molded Bayblend® (ABS & polycarbonate) & ABS		
Vacuum Noise Rating				
Operators position decibel rating		69 dBA		
Machine Dimensions				
Length		13-inch/ 330 mm		
Machine Width		12-inch/ 305 mm	15-inch/ 380 mm	18-inch/ 455 mm
Height		44-inch/ 1115 mm		
Weight (w/cord)		17.9 lb/ 8.1 kg	18.4 lb/ 8.3 kg	18.4 lb/ 8.3 kg
Weight (w/o cord)		16.6 lb/ 7.5 kg	17.1 lb/ 7.7 kg	19.2 lb/ 8.7 kg
Handle weight		2.5 lb/ 1.1 kg		
Debris Recovery/ Filtration				
Vacuum bag capacity		1.2 gallon/ 4.5 liter		
Vacuum bag description		3-ply paper micro filter bag w/ "Bag Full/Blockage" indicator light		
Vacuum filtration		Standard 5-level filtration: 3-play paper filter bag, washable foam intake filter, 3M Filtrete®, exhaust microfilter together yield 98% @ 0.3 micron size filtration		
Recovery System				
Vacuum hose length		15-inch/ 380 mm: stretches to 63-inch/1600 mm		
Vacuum wand		Telescopic 21-inch/ 533 mm to 35-inch/ 890 mm		
Power Cord				
Power cord length		49 ft/ 14935 mm		
Power cord type		17 gauge, 3 wire SJT, safety yellow, UL-listed		
Warranty		1 YEAR ON PARTS AND LABOR. 1 YEAR ON ROTATIONALLY-MOLDED POLYETHYLENE TANKS. NO TRAVEL. 3 YEARS LIMITED WARRANTY ON ELECTRIC MOTOR AND BELTS NOT SUBJECT TO WEAR. PLEASE CONTACT COMPANY FOR MORE WARRANTY INFORMATION.		