

# V-LWU-13 | LIGHT-WEIGHT UPRIGHT VACUUM



**Combining a high performance clean with ultra light, user-friendly design.**

## **Proven performance**

Standard with HEPA 2-stage filtration for improved air quality, the vacuum's cleaning performance is also certified Gold by the Carpet and Rug Institute's (CRI) Seal of Approval program.

## **Increased ease-of-use**

Easily transportable 8lb/3.6kg vacuum easily maneuvers to help minimize operator fatigue and is up to two times lighter than many competitive models. Clean a variety of flooring surfaces quickly and efficiently with flexible settings and adjustable sound level.

## **Reliable durability**

Major components have been proven in commercial application for over five years. Balancing the performance, durability, low operating costs and reduced weight of this vacuum makes it a great value at an affordable price.

## **Key Product Features**

- Maximize cleaning efficiency with automatic pile height adjustment that adapts to a variety of floor surfaces and reduces premature brush wear.
- Clean without disruption in noise-sensitive environments using quiet mode, at less than 70 dBA sound level.
- Reduce maintenance costs and downtime with no-tool brush replacement.

# V-LWU-13 | LIGHT-WEIGHT UPRIGHT VACUUM



FEATURES	SPECIFICATIONS*
<b>Product Name</b>	V-LWU-13
<b>Vacuum System</b> Airflow at 2 in / 50 mm orifice, high speed Vacuum motor hp Vacuum motor type Vacuum motor amps Water lift at sealed orifice	106 cfm / 3 m <sup>3</sup> /m  1.6 hp / 1.19 kW Single stage, thermal protected, direct air 6 A 71 in / 1804 mm
<b>Brush Drive System</b> Brush belt description Brush type Brush size Brush height	Round drive belt 13 in / 330 mm wooden brush roll with natural bristles 2.25 / 57 mm in diameter Automatic, self-adjusting
<b>Filtration</b> Double filtration system Double filtration description Vacuum bag capacity	HEPA paper bag, cloth bag High efficiency (99.97%) at 0.3 micron Fill design, 11.3 qt / 10.7 L
<b>Electrical</b> Power cord length	50 ft / 15 m, 3 wire commercial safety-yellow cord with thermal protection switch
<b>Chassis/Body Construction</b> Construction	Injection molded ABS
<b>Dimensions / Weight / Sound Level</b> Length Width Height Weight Sound level (at operator's ear), low speed	13 in / 330 mm 14.75 in / 370 mm 44 in / 1120 mm 8 lb / 3.6 kg < 70 dBA
<b>Approvals</b>	UL, CRI SOA Gold
<b>Warranty</b>	See your sales representative or authorized distributor for complete warranty details.

\*Specifications subject to change without notice