



## V-LWU-13B | BATTERY UPRIGHT VACUUM

### SALIENT CHARACTERISTICS

#### FOR AN UPRIGHT COMMERCIAL VACUUM

1. The vacuum shall have a 13"/330 mm cleaning path
2. The unit shall not exceed 11 lbs/5.9 kg in weight.
3. The unit shall have a minimum airflow of 50-60 cfm/1.4-1.7 m<sup>3</sup>/m.
4. The upper handle shall be a loop style and ergonomic design for operator comfort.
5. The vacuum shall have automatic pile-height adjustment.
6. The vacuum will have a foot latch mechanism.
7. The vacuum shall have a squeegee blade to aid in hard floor cleaning.
8. Power source shall be 44 VDC / 2.9 Ah lithium ion battery
9. The batteries must be interchangeable.
10. The unit shall have the ability to get noise level below 70 dBa at the operator's ear.
11. The vacuum shall come standard with 2-stage filtration (cloth filter bag, HEPA paper bag) and shall collect dust particles down to 0.3 micron in size and be 99.97% efficient.
12. The vacuum shall meet UL and CSA electrical standards.
13. The vacuum shall have a Carpet and Rug Institute (CRI) Seal of Approval Bronze rating.
14. The warranty of this unit shall be 1 year parts/1 year labor/1 year on battery.
15. It shall be equipped with an operator manual and spare parts listing.
16. The vacuum shall be the manufacturers' standard unit.